

S372 | 37" TWO HEAD WIDEBELT SANDER

Accomplish your tasks without worrying about the performance of your sander.

The Cantek S372 37" Two Head Widebelt Sander is perfect for any small to mid-sized shop looking to achieve outstanding results. Its robust construction is the best in its class and provides superior sanding results. The flexibility with quick-change abrasive belts allows for more applications in a shorter time frame, helping to assist and meet deadlines. In addition, the S372 has a relatively small footprint providing greater access for smaller shops to accomplish bigger results. Equipped with motorized thickness adjustment with digital input control with settings to 0.001" / 0.01mm for precise table setting without compromise.



Key Advantages.

- Dual sanding heads increase efficiency by reducing the number of passes.
- Rubber contact drum for calibration sanding.
- Combination sanding unit with 5" rubber contact drum and 2" wide adjustable sanding platen for a wide range of sanding applications.
- Adjustable platen produces superior sanding results with finer sandpaper grits.
- Accurate digital thickness control with both Inch & Metric settings allows the operator to key in the desired thickness, and table will automatically move into position.
- Two sanding heads:
 - First Head: Rubber contact drum with 7" diameter drum.
 - Second Head: Combination head with 5" diameter drum and 2" wide platen.
- Electronic belt tracking for optimum belt life and sanding results.
- Ammeter for load monitoring to ensure the proper amount of material is removed according to the selected grit.
- Disc brake on the main motor allows for faster belt changes.
- Pneumatic belt tensioning w/ quick release outboard support to facilitate fast belt changes.
- Table raising jackscrews.
- Material over-height limit switch.
- Interlocks are located on all access doors.

Specifications.

Abrasive belt size	37" x 60"
First main motor	20 HP
Feed motor	1HP
Table rise/fall motor	0.25 HP
Working width	37"
Minimum part length	12.5"
Maximum thickness opening	5"
Feed speed: variable	15 to 49 FPM
Pass line height	37"
Dust outlet	6 @ 4"
Compressed air pressure	PSI 60
Compressed air volume	12 CFM
Dust collection requirements	2472 CFM
Net weight	3086 lbs
Machine dimensions	60" X 53" X 67"

STOCK SPECIAL

Stock Special Price

\$23,950.00

Only 8 in stock!

Regular price: \$27,300.00
Electrics: 230/3/60

FOB Blaine, WA (3), Anaheim, CA (1), or Blaine, WA (4)
Price is in US funds. Valid on stock machines only.

Stock subject to prior sale.
State sales taxes extra, if applicable.
E & OE

For more information, contact:

Roberto Phillips

robertop@cantekamerica.com

1.888.982.2683 ext.5049

Cantek America Inc.

www.cantekamerica.com

PMB #104 1124 Fir Avenue | Blaine, WA 98230