

EDITION 4.4 SERVO

HOMAG Edgebanding Machine



Pre-milling unit with Diamond inserts. 100 mm diameter.

PRECISION, CAPABILITY & FLEXIBILITY

The Edition program sets a new industry standard by innovatively combining the best of all worlds into a durable, adaptable, and reliable series of machinery solutions for any application. HOMAG designed this program for the world market to take advantage of economies of scale. At the same time, Stiles has specifically tailored the program with features to fit the unique demand of the U. S. market.

The Edition **4.4 Servo** is designed for companies looking to process coil material (0.4–3 mm) and thin strips (0.4–8 mm) with fast, automatic changeover from the machine control.



Nested top fine trim with 3 roller tracing.

FEATURES:

- Rigid, welded steel frame
- Servo-controlled positioning of infeed fence, pressure zone, fine trim and profile scraping unit
- Multiple profile fine trim and profile scraping unit
- High flexibility for all edge types
- Precision-controlled edge feeding to reduce wasted material
- 22" FULL-HD operating touch screen
- Industrial feed track for precision edge quality year after year.
- Panel pre-heating for optimum edge quality.



Standardized Homag powerTouch interface machine control

SPECIFICATIONS:

machine length:	5,573 mm	(18 1/2 ft)
working height:	950 mm	(37 in)
edgeband height	12–65 mm	(1/2 - 2 1/2 in)
variable feed speed:	8 – 14 m/min	(26 – 46 ft/min)
feed speed (with corner trimming):	11 m/min	(36 ft/min)
workpiece thickness:	8–60 mm	(5/16–2 3/8 in)
electrical connection:	208/230/440/480 V / 3-phase / 60 Hz	
dust extraction:	(1x) 120 mm, (3x) 80 mm, (1x) 100, 2,035 CFM	

Talk to us. We're ready to help.

For more information on Homag edgebanding machines, please contact your Regional Product Specialist.

Stiles Machinery Inc. | 616.698.7500 | www.stilesmachinery.com

stiles

Edition 4.4 Servo Machine Drawing

